

Weighing indicator model **ISC-VC**

Simple, compact indicator in stainless steel housing, suitable for many applications!
Supplied with special checkweigh function with automatic color change of displaylighting.



Options a.o.

- thermal receipt printer or thermal labelprinter (various versions)
- virtual printer, model VP-k, memory card saving all printing orders; this information can be transmitted to a PC later
- USB-interface in stead of regular RS-232 interface
- wireless connection from indicator (RS-232) to PC's comport or USB/printer
- alibi memory with date/time, max. 120.000 weighings
- infra red remote with IR-input kit, control up to 8 m
- wireless repeater, model ISC-DB
- radio-interface for wireless connection with PC/printer and indicator
- radio-interface for wireless connection with ISC-DB repeater
- settable setpoints (not in combination with alibi memory)
- simple Windows software for configuring through PC



Option: stainless steel pole

Properties

- versatile weight indicator for high performance, CE verified
- water protected flat 5 keys keypad; functions: zero, tare (manual, automatic, preset) print, on/off, and a function key to which a desired function can simply be linked
- clearly readable backlit LCD display, 25 mm character height
- display with special checkweigh function: too little (display backlight **orange**), too much (**red**) or correct weight (**green**); background lighting color and brightness are adjustable
- stainless steel housing, protection class IP68; included stainless steel wall bracket (for wall mounting or as table stand)
- dim. excluded mounting bracket: 243 x 78,4 x 145 mm (l x d x h)
- 24-bit A/D-converter, 4-chanel; max. 200 conv./sec. autoslect, max. 8 linearisation points
- display resolution up to 10000e or multirange 3 x 3000e (verification ready)
- max. 1.000.000 readable divisions, internal resolution max. 3.000.000 divisions
- number of connectable load cells: 8 (350 Ω) / 16 (700 Ω)
- digital calibration and setup through keypad or optional software "All ScalesTools"
- nett/gross indication in kg or lb; accumulation of weights, recipe weighing, percentage weighing, piece counting function (counting resolution 1.500.000 div), in-/out trucks, hold function, peak level, network function up to 4 indicators, high resolution weighing (10x more accurate reading)
- supplied with 1x RS232/C / RS485 interface for connection to PC, PLC etc.
- supplied with 1x RS232/C interface for connection to (label)printer
- power: 230 V (fixed cord)

Weighing indicator

model **ISC-VC**

Measurement sketch:

