

Weighing indicator

model ISCI-R



Options

- real time clock
- IR remote control with IR-input kit
- thermal receipt printer Citizen
- connection cable RS-232 to PC/printer
- wireless connection to PC-printer
- module with 2 optoisolated digital inputs / 2 fotomosfet outputs, applicable as settable set points / 1,5 mtr. connection cable (not together with alibi memory)
- alibige memory with date/time, max. 120.000 weighings
- radio interface for wireless connection to PC/printer and indicator
- ethernet interface + ethernet cable (1,5 m)

General data

- **CE verified**
- water protected, flat keyboard with 17 keys
- clearly readable, backlit LCD display, 25 mm height
- **stainless steel housing**, protection class IP68, dim. 260 x 175 x 130 mm (w x h x d)
- incl. adjustable wall mounting bracket / table stand
- 24-bit A/D-converter, 4-channel
- display resolution up to 10000e or multirange 3 x 3000e (CE approved)
- internal rechargeable battery (60 h operation time with one 350 Ω load cell)
- number of connectable load cells: 8 (350 Ω) / 16 (700 Ω)
- nett/gross indication in kg or lb
- cumulative weighing, recipe weighing, percentage determination, piece counting, in-/out trucks, hold function, peek value
- network function up to 4 indicators
- 2x RS-232/C port



CE verified, class



(application for legal trade)

