


Compression load cell series ASC



Properties

- capacities from 250 to 100000 kg
- CE-M C3 approved, from 2500 to 12500 kg
- low profile
- great resistance to lateral forces
- stainless steel construction
- IP68 protection
- shielded connection cable
- minimum load cell verification interval: $V_{min} = E_{Max} / 10000$
- full scale output: $2\text{mV/V} \pm 0,5\%$
- non-repeatability: 0,01% F.S.
- combined error 0,05%
- temperature effect on zero: 0,02% / 10°C
- temperature effect on full scale output: 0,02% / 10°C
- compensated temperature range: $-10^\circ\text{C}/+40^\circ\text{C}$
- operating temperature range: $-20^\circ\text{C}/+60^\circ\text{C}$
- creep error after 30 minutes: 0,02% F.S.
- maximum tolerated excitation voltage: 15 Vdc
- input resistance: $750 \pm 10 \text{ Ohm}$
- output resistance: $700 \pm 5 \text{ Ohm}$
- zero balance: +/-1% F.S.
- insulation resistance: >5000 MOhm
- safe overload: 120% F.S.
- 4-wire shielded cable, 5 mm diameter:
 - 5 m long for 250 kg - 5 t versions;
 - 10 m long for 7,5 - 100 t versions.



Also available as an ATEX version for use in hazardous areas.



| type | ASC-250 | ASC-500 | ASC-1000 | ASC-2500 | ASC-5000 | ASC-7500 | ASC-10T | ASC-15T | ASC-30T | ASC-50T | ASC-100T | ASC-200T |
|-------------|---------|---------|----------|----------|----------|----------|---------|---------|---------|---------|----------|----------|
| capacity kg | 250 | 500 | 1000 | 2500 | 5000 | 7500 | 10000 | 15000 | 30000 | 50000 | 100000 | 200000 |
| dim. A mm | 82 | 82 | 82 | 82 | 82 | 82 | 82 | 100 | 126 | 165 | 165 | 175 |
| dim. B mm | 44 | 44 | 44 | 44 | 44 | 44 | 44 | 48,5 | 54 | 80 | 80 | 80 |
| dim. C mm | 32 | 32 | 32 | 32 | 32 | 32 | 32 | 35 | 40 | 60 | 60 | 60 |
| dim. D mm | 22 | 22 | 22 | 22 | 22 | 22 | 22 | 28 | 35 | 60 | 60 | 70 |
| dim. E mm | 12 | 12 | 12 | 12 | 12 | 12 | 12 | 13,5 | 14 | 20 | 20 | 20 |



Compression load cells series ASC

Measurement sketch for capacities

250 - 500 - 1000 - 2500 - 5000 - 10000 - 12500 kg





dimensions in mm



Compression load cells series ASC

Measurement sketch for capacity 15000 kg





dimensions in mm



Compression load cells series ASC

Measurement sketch for capacity 30000 kg





dimensions in mm



Compression load cells series ASC

Measurement sketch for capacities 50000 - 100000 kg



dimensions in mm



Compression load cells series ASC

Measurement sketch for capacity 200000 kg

Dimensions in mm

