

Floor Scale Model **MV** version Heavy Duty



Properties

- **M** not for legal trade or CE verified (application for legal trade)
- for any application; extra rigid construction, painted / enamelled
- custom made capacity on application
- custom made dimensions; practically unlimited possibilities
- equipped with watertight load cells, protection class IP67
- reading of weighing results and operation can be provided by any weight
- indicator from our delivery program
- overload protection
- power 230V (through indicator)

Options i.a.

- dual range division
- infrared remote control
- real-time clock module (date/time)
- external thermal ticketprinter/labelprinter
- wireless connection indicator (RS-232) to USB of PC / printer
- alibi memory incl. date/time for max. 120.000 weighings
- pole for indicator
- ethernet-interface
- USB interface (instead of standard RS-232 interface)
- easy weigh software for Windows
- connection cable from RS-232 to PC/printer (approx. 1.5m)
- WiFi-interface through acces point (WiFi IEEE 802.11b)
- BlueTooth interface (2.0 +EDR)
- different indicator
- connection cable from USB to USB of PC (approx. 1.5m, art. AC143 needed)
- USB HID interface cable (approx. 1.5m)
- incorporated USB-kit, incl. USB memorycard (2GB) for PC
- radio-interface for the purpose of wireless connection to PC/printer and indicator, max. distance 70 m indoors/ 150 m outdoors
- ethernet-interface
- expansion module with indicator-LEDs for checkweighing (under/over/ok)

